

# Sealing bead

Self-adhesive foamed PUR seal



RoHS  
compliant

REACH  
COMPLIANCE

At the underside of the KDR-BMP enclosure base plates a foamed PUR seal is attached. We now also offer these PUR seals separately for individual applications.

The PUR seal is applied to a carrier film that is self-adhesive on one side and is available in 2 widths. The length is 2150 mm each. The height of the seal results from the respective width. The PUR seal is easy to compress and has very good resilience.

Installing the PUR seal is very easy: remove the protective film, stick it on, done!

## Specifications

<b>Material</b>	PU foam
<b>Operating temperature</b>	-40 C° to 80 C°
<b>Properties</b>	halogen free, silicone free

## Advantages & Benefits

- Very simple and quick installation
- Easy laying around corners
- Very good resilience

## Product Types & Sizes

Sealing bead 6×3,5



Part No.	<b>43347</b>
EAN	<b>4251269332</b>
	<b>784</b>
Package quantity	<b>1</b>
Length	<b>2.150 mm</b>
Width	<b>6 mm</b>
Height	<b>3,5 mm</b>

Sealing bead 9x5



Part No.	<b>43348</b>
EAN	<b>4251269332</b>
	<b>777</b>
Package quantity	<b>1</b>
Length	<b>2.150 mm</b>
Width	<b>9 mm</b>
Height	<b>5 mm</b>

---

**icotek**<sup>®</sup>  
smart cable management